MAINTAIN STOCKTANKS

FILTRATION

This is the most important, By having good circulation in the tank, chemicals, acids are much less likely to damage the galvanized coating

CHEMICALS

1.Tankkd Zero Chlorine products

We advice you to use these products to lower the change of oxidation true chemicals

2. Products Chlorine based

Use slow chlorine tabs in a floater

- 1. Start up your Tankkd
- 2. Measure with a test strip
- 3. calculate the volume of your tank
- 4. Check your Alkaliniti between 80 and 100ppm

add Alkalinity up if needed (dissolve this product in water before adding to the tank)

- 5. Check your PH needs to be between 7,2 and 74
- 6. Add ph up or down in liquid if needed.
- 7. Add the right amount of Tankkd zero chlorine or put your slow chlorine tab in a floater.
- 8. Test the water weakly
- 9. Add products if needed

With the zero chlorine treatment use weakly oxy pool

Always wait 30 minutes before taking a dip

Always keep the pump running when adding chemicals.

HOW TO

Use a sand filter with min capacity 1500gal

Summer 8hours each day

Winter 3 hours each day

Use cotton balls instead of sand/alass

Wash the cotton balls every month on 30 degrees without product,let them dry in open air

If the tank has dirt from transport such as a black spots or a scratch. Use the melamine Sponge and oil to polish it.

WINTER

If you decide not to use the tank, you can choose to leave the water in and let the filter system run for 2 hours a day. Do not add any chemicals. When it freezes, switch off the pump and close the taps on the tank. The water may remain in the tank. When it stops freezing, plug everything back in. Before you go back to splashing, we recommend that you let the water out of the tank and start it up again with fresh water.

If you prefer to drain the water from the tank after the summer, this is possible. Then rinse the tank thoroughly and wash it with a soft soap. Dry the tank and make sure it is covered. So that no acid from rain or leaves is formed in the tank.

If you have a heather on the tank, you can continue to use it. Just make sure that the water cannot freeze in the pump or heater.

CLEANING YOUR TANK

Use a Melamine Sponge to rub of lime, grease, dirt

rub the outside of the tank monthly with a soft oil. If you empty the tank in the winter, rinse it very well first. Wash it with a soft soap. Dry the tank and also rub the inside with an oil without alcohol

